

Paint recommendation: Mineral substrates



Substrates	Primer/surfacer	Topcoats	Clearcoats
Concrete / cement / stone	▶ 2K Primer High Build / 2K EP Primer High Build, binder / topcoat thinned (EP, PUR)	Primers / surfacers can be coated with following topcoats 2K topcoats: EP (interiors), PUR, PUR TEX Fine (structure), PUR MATT Application with different gloss levels and structure effects possible Direct coating of substrates after consulting and test coating	2K clearcoat for all 2K topcoats Direct coating of substrates after consulting and test coating
Roofing tiles / clay	▶ 2K Primer High Build		
Ceramic tiles / wall tiles / cement-based composition floors	▶ 2K EP Primer High Build, EP binder / topcoat thinned		

Pre-treatment: Mineral substrates



Pre-treatment of substrates

Concrete / cement

Dry (at least 3 months old), possible fluosilicate sealing. No concrete refurbishment!

Decreasing

Suitable cleaning / degreasing agents: E.g. solvents, alcohols, silicone remover

Cleaning

Dust-free

Sand thoroughly

Depending on substrate

Ceramic tiles / wall tiles

Only decorative coating (depending on substrate)

Suitable cleaning / degreasing agents: E.g. solvents, alcohols, silicone remover

multimix

Standex GmbH · Christbusch 45 · 42285 Wuppertal · Germany